

# MAFCO – BITUMUL - C

## **Product Description:**

Mafco Bitumul C is a heavy duty clay stabilized with a general purpose bitumen emulsion.

## **Intended Uses:**

Is a general purpose water proofing compound and can be applied in almost all surfaces such as brick, concrete, asbestos cement, tiles, metal surfaces and bitumen.

## **Advantages:**

High resistance to water vapor.  
Good bonding to all surfaces.  
Nontoxic.  
Seamless finish.  
Easy to apply.  
High stability.

## **Application:**

Clean the surface thoroughly before application.  
If there are any cracks fill them properly.  
If the surface was highly porous apply one coat primer that contains diluted Mafco Bitumul C with pure water ( dilution ratio 1:2 max).  
Allow the primer to cure and apply two coats of Mafco Bitumul C.

## **Storage:**

Store in closed container in shaded area.  
If it is properly stored, it will last for one year.

## **Packing:**

( 200 Liter Drums / 20 Liter Pails )

## **Health and Safety:**

Nonflammable, nontoxic.  
Avoid prolonged contact with skin.  
If eyes are contacted, irrigate with cold water.

Disclaimer: The information given in this sheet is for guidance only. Any person using this product without first making further enquiries as to the suitability of the product for the intended purpose does so at his own risk and we can accept no liability for the performance of the product or for any loss or damage arising out of such use. This technical data sheets supersede the previous technical data sheets, and the information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.



***Pioneers in Bitumen***

## MAFCO – BITUMUL - C

### **Standard:**

ASTM D-1227.

### **Technical Data:**

Solid content	: 55-62 % by wt.
Specific gravity	: 1.00
Drying time to touch	: 4 hrs.
Curing time complete	: 24 hrs.
Heat resistance at 100 deg C	: No flow.
Ash content	: 10 max.

Disclaimer: The information given in this sheet is for guidance only. Any person using this product without first making further enquiries as to the suitability of the product for the intended purpose does so at his own risk and we can accept no liability for the performance of the product or for any loss or damage arising out of such use. This technical data sheets supersede the previous technical data sheets, and the information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.



***Pioneers in Bitumen***