

# MAFCO – OXIDIZED BITUMEN – 115 / 15

## **Product Description:**

Bitumen 115/15 is manufactured from selected grade bitumen oxidize using suitable catalytic agent at controlled temperature to obtain stipulated standard.

## **Intended Uses:**

For water proofing roofs.  
Foundation above and below ground level.  
For pipe joints.  
To manufacture paints and primers.

## **Advantages:**

Can be applied at any thickness.  
Excellent waterproofing property.  
Good binding to all surfaces.  
Seamless work.

## **Application:**

Clean the surface thoroughly without any dirt, loose particles, grease or oil.  
Apply one coat of Mafco Fast Primer.  
Then apply first coat Bitumen 115/15.  
Successive coat can be applied within 10 minutes.  
Use mop or brush.

## **Safety:**

As heating is required, use goggles, hand gloves, safety shoes and protective clothing. In case of accident immediately irrigate with cold water and call for medical aid.

## **Standard:**

ASTM D-312 and BS 3690.

## **Packing:**

(140-180 kg Drum / 18 kg Pail )

## **Technical Data:**

Softening point deg C	: 110 – 120
Penetration at 25 deg C	: 10 – 20
Solubility in trichloroethylene	: 99 min
Water content	: Nil

Disclaimer: The information given in this sheet is for guidance only. Any person using this product without first making further enquiries as to the suitability of the product for the intended purpose does so at his own risk and we can accept no liability for the performance of the product or for any loss or damage arising out of such use. This technical data sheets supersede the previous technical data sheets, and the information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.



**Pioneers in Bitumen**